



Empfohlene Einbaulage: Welle horizontal

|   |     |                      |    |  |    |      |    |                 |  |
|---|-----|----------------------|----|--|----|------|----|-----------------|--|
| 900   | 895 | 1000                 | 60 | 958  | 24 | 14   | 22 | 165             |  |
| 800   | 795 | 900                  | 60 | 861  | 24 | 14   | 22 | 138             |  |
| 710   | 705 | 810                  | 60 | 775  | 16 | 14   | 22 | 102             |  |
| 630   | 625 | 730                  | 50 | 698  | 16 | 14   | 22 | 78              |  |
| 500   | 495 | 580                  | 50 | 551  | 12 | 11,5 | 17 | 55              |  |
| 450   | 445 | 530                  | 50 | 497  | 12 | 11,5 | 17 | 47              |  |
| 400   | 395 | 480                  | 50 | 448  | 12 | 11,5 | 17 | 39              |  |
| 355   | 350 | 435                  | 50 | 405  | 8  | 11,5 | 17 | 33              |  |
| 315   | 310 | 395                  | 40 | 366  | 8  | 11,5 | 17 | 27              |  |
| 300   | 290 | 380                  | 40 | 349  | 8  | 11,5 | 17 | 25              |  |
| 280   | 275 | 360                  | 40 | 332  | 8  | 11,5 | 17 | 22              |  |
| 250   | 245 | 320                  | 40 | 292  | 8  | 11,5 | 17 | 19              |  |
| 224   | 220 | 294                  | 40 | 265  | 8  | 11,5 | 14 | 16              |  |
| 200   | 195 | 270                  | 40 | 241  | 8  | 11,5 | 14 | 13              |  |
| 180   | 175 | 250                  | 30 | 219  | 8  | 11,5 | 14 | 10              |  |
| 160   | 155 | 230                  | 30 | 200  | 8  | 11,5 | 14 | 9,5             |  |
| 150   | 145 | 215                  | 30 | 191  | 8  | 11,5 | 14 | 9,0             |  |
| 125   | 120 | 185                  | 30 | 165  | 4  | 9,5  | 14 | 6,5             |  |
| 112   | 105 | 172                  | 30 | 151  | 4  | 9,5  | 14 | 6,0             |  |
| 100   | 95  | 162                  | 30 | 139  | 4  | 9,5  | 14 | 5,1             |  |
| 90  | 85  | 155                  | 30 | 128  | 4  | 9,5  | 14 | 4,6             |  |
| 80  | 75  | 142                  | 30 | 118  | 4  | 9,5  | 14 | 4,0             |  |
| 71  | 65  | 125                  | 30 | 110  | 4  | 9,5  | 14 | 3,5             |  |
| DN  | Di  | Da                   | B  | Lk   | n  | ød   | SW | kg (nur Klappe) |  |
| <b>AGS-Stellantriebe GmbH</b><br>Görlitzer Str. 2<br>D - 33758 Schloß Holte |     | Datum:<br>30.03.2013 |    | Ringdrosselklappe RDB-LK<br>Flansanschluss n. DIN 24154 R2 |    |      |    | <b>37520.03</b> |  |