

Butterfly valve RDO

	<p><u>Nominal sizes:</u> DN 32 to DN 600</p>						
	<p><u>Flange connection:</u> To be mounted between flanges PN6-16 n. DIN 2631 - 2633</p>						
	<p><u>Temperature range</u> Up to 550°C</p> <p>The temperature resistance depends on the pressure.</p>						
	<p><u>Valve types:</u></p> <table border="0"> <tr> <td>Swing-through</td> <td>Leakage ~1% (KVS-Value)</td> </tr> <tr> <td>Stop bar</td> <td>Leakage ~0,5% (KVS-Value)</td> </tr> <tr> <td>Stop bar + packing insert</td> <td>Leakage ~0,3% (KVS-Value)</td> </tr> </table> <p>Leakage depends on temperature, pressure and nominal size</p>	Swing-through	Leakage ~1% (KVS-Value)	Stop bar	Leakage ~0,5% (KVS-Value)	Stop bar + packing insert	Leakage ~0,3% (KVS-Value)
Swing-through	Leakage ~1% (KVS-Value)						
Stop bar	Leakage ~0,5% (KVS-Value)						
Stop bar + packing insert	Leakage ~0,3% (KVS-Value)						
	<p><u>Materials:</u></p> <table border="0"> <tr> <td>Housing:</td> <td>GG25 / GGG40</td> </tr> <tr> <td>Valve plate :</td> <td>Ms / St37 / 1.4301</td> </tr> <tr> <td>Shaft</td> <td>Ms / 1.4305</td> </tr> </table> <p>Other materials on request</p>	Housing:	GG25 / GGG40	Valve plate :	Ms / St37 / 1.4301	Shaft	Ms / 1.4305
Housing:	GG25 / GGG40						
Valve plate :	Ms / St37 / 1.4301						
Shaft	Ms / 1.4305						
	<p><u>Shaft sealings:</u> adjustable packing box or O-rings</p>						
	<p><u>Variants:</u> manual, electric, pneumatic</p>						