



Empfohlene Einbaulage: Welle horizontal

Zum Einklemmen zwischen Flansche PN6 o. PN10 n. DIN EN 1092-1, andere PN auf Anfrage

| | | | | | | | | | |
|---|-----|----------------------|--|-----------|-----|-----|-----------------|------|--|
| 1000 | 990 | 50 / 60 | 1090 | 1120 | 645 | 630 | 22 | 190 | |
| 900 | 890 | 50 / 60 | 990 | 1015 | 590 | 575 | 22 | 155 | |
| 800 | 790 | 50 / 60 | 890 | 915 | 540 | 525 | 22 | 130 | |
| 700 | 690 | 50 / 60 | 780 | 810 | 480 | 465 | 22 | 98 | |
| 600 | 590 | 50 | 675 | 695 | 420 | 405 | 22 | 76 | |
| 500 | 490 | 50 | 575 | 590 | 365 | 355 | 17 | 55 | |
| 450 | 440 | 50 | 530 | 535 | 355 | 340 | 17 | 47 | |
| 400 | 390 | 50 | 470 | 485 | 315 | 300 | 17 | 39 | |
| 350 | 340 | 50 | 420 | 435 | 285 | 270 | 17 | 32 | |
| 300 | 295 | 40 | 370 | 375 | 255 | 240 | 17 | 25 | |
| 250 | 249 | 40 | 315 | 325 | 230 | 215 | 17 | 19 | |
| 200 | 199 | 40 | 260 | 270 | 200 | 185 | 14 | 12 | |
| 175 | 174 | 30 | 235 | 245 | 190 | 175 | 14 | 10,5 | |
| 150 | 149 | 30 | 205 | 215 | 175 | 160 | 14 | 9,0 | |
| 125 | 124 | 30 | 180 | 190 | 155 | 140 | 14 | 6,5 | |
| 100 | 99 | 30 | 150 | 160 | 140 | 125 | 14 | 5,1 | |
| 80 | 79 | 30 | 130 | 140 | 130 | 115 | 14 | 4,0 | |
| 65 | 64 | 30 | 115 | 125 | 125 | 110 | 14 | 3,0 | |
| 50 | 49 | 30 | 95 | 105 | 115 | 100 | 14 | 2,8 | |
| 40 | 40 | 30 | 85 | 90 | 105 | 90 | 14 | 2,3 | |
| 32 | 32 | 30 | 75 | 80 | 100 | 85 | 14 | 2,1 | |
| DN | DI | B | DA (PN6) | DA (PN10) | C | C1 | SW | kg | |
| AGS-Stellantriebe GmbH Görlitzer Str. 2 D - 33758 Schloß Holte | | Datum: 02.06.2020 | Ringdrosselklappe RDB-L PN6/10, mit Aufbaukonsole T300 | | | | 37100.03 | | |