



Empfohlene Einbaulage: Welle horizontal

Zum Einklemmen zwischen Flansche PN6/10 n. DIN 2631/2632, andere PN auf Anfrage

1000	990	60	1090	1124	645	22	200	
900	890	60	990	1017	590	22	165	
800	790	60	890	917	540	22	138	
700	690	60	780	810	480	22	102	
600	590	50	675	695	420	22	76	
500	490	50	575	590	365	17	55	
450	440	50	525	538	340	17	47	
400	390	50	470	480	315	17	39	
350	340	50	420	435	285	17	32	
300	295	40	370	375	255	17	25	
250	249	40	315	325	230	17	19	
200	199	40	260	270	200	14	12	
175	174	30	235	245	188	14	10,5	
150	149	30	205	215	175	14	9,0	
125	124	30	180	190	155	14	6,5	
100	99	30	150	160	140	14	5,1	
80	79	30	130	140	130	14	4,0	
65	64	30	115	125	125	14	3,0	
50	49	30	95	105	115	14	2,8	
40	40	30	85	90	105	14	2,3	
32	32	30	75	80	100	14	2,1	
25	32	30	75	80	95	14	2,1	
DN	DI	B	DA (PN6)	DA (PN10)	C	SW	kg (nur Klappe)	
AGS-Stellantriebe GmbH Görlitzer Str. 2 D - 33758 Schloß Holte		Datum: 22.10.2015	Ringdrosselklappe RDB-L mit T-Konsole				37100.03	