



Empfohlene Einbaulage: Welle horizontal

900	895	1000	60	958	24	14	22	165	
800	795	900	60	861	24	14	22	138	
710	705	810	60	775	16	14	22	102	
630	625	730	50	698	16	14	22	78	
500	495	580	50	551	12	11,5	17	55	
450	445	530	50	497	12	11,5	17	47	
400	395	480	50	448	12	11,5	17	39	
355	350	435	50	405	8	11,5	17	33	
315	310	395	40	366	8	11,5	17	27	
300	290	380	40	349	8	11,5	17	25	
280	275	360	40	332	8	11,5	17	22	
250	245	320	40	292	8	11,5	17	19	
224	220	294	40	265	8	11,5	14	16	
200	195	270	40	241	8	11,5	14	13	
180	175	250	30	219	8	11,5	14	10	
160	155	230	30	200	8	11,5	14	9,5	
150	145	215	30	191	8	11,5	14	9,0	
125	120	185	30	165	4	9,5	14	6,5	
112	105	172	30	151	4	9,5	14	6,0	
100	95	162	30	139	4	9,5	14	5,1	
90	85	155	30	128	4	9,5	14	4,6	
80	75	142	30	118	4	9,5	14	4,0	
71	65	125	30	110	4	9,5	14	3,5	
DN	Di	Da	B	Lk	n	ød	SW	kg (nur Klappe)	
AGS-Stellantriebe GmbH Görlitzer Str. 2 D - 33758 Schloß Holte		Datum: 30.03.2013		Ringdrosselklappe RDB-LK Flansanschluss n. DIN 24154 R2				37520.03	