



Empfohlene Einbaulage: Welle horizontal

1500	1620	140	1575	40	18	27	10	222
1400	1520	140	1475	32	18	27	10	196
1250	1370	140	1337	32	18	22	10	168
1120	1240	140	1200	32	18	22	10	128
1000	1100	100	1067	24	14	22	8	108
900	1000	100	958	24	14	22	8	84
800	900	100	861	24	14	22	8	68
710	810	100	775	16	14	22	8	54
630	730	100	698	16	14	22	8	44
600	700	100	665	16	14	22	8	41
560	660	100	629	16	14	17	8	38
500	580	65	551	12	11,5	17	8	32
450	530	65	497	12	11,5	17	8	26
400	480	65	448	12	11,5	17	8	19
355	435	65	405	8	11,5	17	8	16
315	395	65	366	8	11,5	17	8	13
300	380	60	349	8	11,5	17	8	12
280	360	60	332	8	11,5	17	8	11
250	320	60	292	8	11,5	17	6	8,5
224	295	60	265	8	11,5	17	6	7,8
200	270	60	241	8	11,5	14	6	7,0
160	230	60	200	8	11,5	14	6	6,0
150	215	60	191	8	11,5	14	6	5,2
140	205	60	182	8	11,5	14	6	4,8
125	185	60	165	4	9,5	14	6	4,2
112	172	60	151	4	9,5	14	6	3,6
100	160	60	139	4	9,5	14	6	3,2
90	150	60	128	4	9,5	14	6	2,9
80	140	60	118	4	9,5	14	6	2,7
DN	DA	B	Lk	n	ød	SW	s	kg

AGS-Stellantriebe GmbH
Görlitzer Str.2
D - 33758 Schloß Holte

Datum:
21.07.2020

Flanschdrosselklappe FDB-LK
Flansche n. DIN 24154 R2

37500.03